

### GREEN LABEL LIST

[illegible]



No Lesen : ELJ0004001

Licence No :

## LESEN PENSIJILAN EKO-LABEL

### *Eco-Label Licence*

SIRIM  
ECO-LABEL

SIRIM QAS International Sdn. Bhd. dengan ini menganugerahkan kepada  
SIRIM QAS International Sdn. Bhd. hereby grants to

JOTUN PAINTS (M) SDN. BHD.  
LOT 7, PERSIARAN PERUSAHAAN  
SEKSYEN 23  
40300, SHAH ALAM  
SELANGOR, MALAYSIA

Lesen untuk menggunakan Tanda Eco-Label di atas barangan  
*a licence to use the Eco-Label Mark on*


**PAINTS**

Please refer to detail in the SCHEDULE

sebagai mematuhi keperluan  
*as complying with*

SIRIM CRITERIA 019 : 2012

Khalidah Mustafa  
Pengarah Urusan  
Managing Director  
SIRIM QAS International Sdn. Bhd.



SIRIM QAS International Sdn. Bhd.  
(No. Syarikat 410334-X)  
1, Persiaran Dato' Menteri  
Seksyen 2, Peti Surat 7035  
40700 Shah Alam  
Selangor Darul Ehsan  
MALAYSIA.

Tel : 60-3-55446400  
Faks : 60-3-55446466

<http://www.sirim.my>  
<http://www.malaysian-certified.my>

Tarikh Mula Pensijilan : 20 November 2009

*Certified Since*

Sah Sehingga : 19 November 2017

*Valid Until*

Tarikh Dikeluarkan : 21 January 2016

*Issue Date*

No Siri : 021668

*Serial No*

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM QAS International Sdn. Bhd.  
*This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM QAS International Sdn. Bhd.*

## SCHEDULE

### JOTUN PAINTS (M) SDN. BHD.



SIRIM  
ECO-LABEL

|       |                                                                        |
|-------|------------------------------------------------------------------------|
| Brand | : MAJESTIC                                                             |
| Model | : MAJESTIC OPTIMA, MAJESTIC PEARL SILK, MAJESTIC ROYALE MATT           |
| Type  | : LATEX EMULSION PAINT FOR INTERIOR USE                                |
| Brand | : MAJESTIC                                                             |
| Model | : MAJESTIC TRUE BEAUTY SHEEN, MAJESTIC TRUE BEAUTY MATT                |
| Type  | : LATEX EMULSION PAINT FOR INTERIOR AND EXTERIOR USE                   |
| Brand | : MAJESTIC                                                             |
| Model | : MAJESTIC PRIMER                                                      |
| Type  | : WATER BASED SEALER                                                   |
| Brand | : JOTASHIELD                                                           |
| Model | : JOTASHIELD, JOTASHIELD EXTREME, JOTASHIELD SILICONE, JOTASHIELD FLEX |
| Type  | : LATEX EMULSION PAINT FOR INTERIOR AND EXTERIOR USE                   |
| Brand | : JOTASHIELD                                                           |
| Model | : JOTASHIELD PRIMER 07                                                 |
| Type  | : WATER BASED SEALER                                                   |
| Brand | : STRAX                                                                |
| Model | : STRAX                                                                |
| Type  | : LATEX EMULSION PAINT FOR INTERIOR USE                                |
| Brand | : GARDEX                                                               |
| Model | : GARDEX ECOGLOSS                                                      |
| Type  | : LATEX EMULSION PAINT FOR INTERIOR AND EXTERIOR USE                   |
| Brand | : GARDEX                                                               |
| Model | : GARDEX ECOPRIMER                                                     |
| Type  | : WATER BASED SEALER                                                   |
| Brand | : JOTAPLAST                                                            |
| Model | : JOTAPLAST, JOTAPLAST MAX                                             |
| Type  | : LATEX EMULSION PAINT FOR INTERIOR USE                                |
| Model | : JOTAROOF, JOTATOUGH HISHIELD                                         |
| Type  | : LATEX EMULSION PAINT FOR INTERIOR AND EXTERIOR USE                   |

SIRIM QAS International Sdn. Bhd.  
(No. Syarikat 410334-X)  
1, Persiaran Dato' Menteri  
Seksyen 2, Peti Surat 7035  
40700 Shah Alam  
Selangor Darul Ehsan  
MALAYSIA.

Tel : 60-3-55446400  
Faks : 60-3-55446466

<http://www.sirim.my>  
<http://www.malaysian-certified.my>

Tarikh Mula Pensijilan : 20 November 2009

*Certified Since*

Sah Sehingga : 19 November 2017

*Valid Until*

Tarikh Dikeluarkan : 21 January 2016

*Issue Date*

No Siri : 021668

*Serial No*

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM QAS International Sdn. Bhd.  
*This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM QAS International Sdn. Bhd.*

## SCHEDULE

JOTUN PAINTS (M) SDN. BHD.



SIRIM  
ECO-LABEL

Model : BASECOAT SEALER, JOTASEALER 03  
Type : WATER BASED SEALER

Eco-Labeling Claim : LOW VOC

---

End of page

SIRIM QAS International Sdn. Bhd.  
(No. Syarikat 410334-X)  
1, Persiaran Dato' Menteri  
Seksyen 2, Petai Surat 7035  
40700 Shah Alam  
Selangor Darul Ehsan  
MALAYSIA.

Tel : 60-3-55446400  
Faks : 60-3-55446466

<http://www.sirim.my>  
<http://www.malaysian-certified.my>

Tarikh Mula Pensijilan : 20 November 2009

*Certified Since*

Sah Sehingga : 19 November 2017

*Valid Until*

Tarikh Dikeluarkan : 21 January 2016

*Issue Date*

No Siri : 021668

*Serial No*

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM QAS International Sdn. Bhd.  
*This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM QAS International Sdn. Bhd.*



## Gardex EcoGloss

---

### Product description

#### Type

A premium and environment-friendly water-based acrylic enamel paint for wood and metal. It provides better indoor air quality and reduces environmental impact.

#### Features and benefits

Ultra Low VOC - Surpasses international and local green buildings certification to provides better air quality indoors and outdoors.

Low Odour - Paint odour is low during and after application making the property ready for occupancy in shorter period.

Fast Drying - Convenient and quick drying solution that saves time, energy and manpower.

Excellent Colour Last - Durable colours and gloss finish that keeps the property looking new over time for a longer repainting period.

Non-Yellowing - Maintains whiteness and original colour far better than oil-based paint.

Anti Fungal - Prevents unsightly growth of surface fungus to maintain beautiful and healthy wood.

Anti Rust - Extends the beauty and durability of metal by protecting it from corrosion.

Formulated without Harmful Chemicals - Free from harmful chemicals such as APEO, formaldehyde, heavy metals and has low volatile organic compound (VOC).

#### Recommended use

Ideally for interior application, suitable for both new and painted substrate.

#### Substrate

On wood and metal surfaces.

---

### Product data

|                       |                                                                                       |
|-----------------------|---------------------------------------------------------------------------------------|
| <b>Packaging size</b> | 5L                                                                                    |
| <b>Colours</b>        | As per colour card and available in Jotun Multicolor tinting system (Interior range). |
| <b>Solids</b>         | 33 ± 2 volume%                                                                        |

---

### Application data

#### Remarks

Handle with care. Stir well before use.

#### Application methods

---

By brush, roller, airless spray or conventional spray.

### Guiding data for airless spray

|                     |                                         |
|---------------------|-----------------------------------------|
| Nozzle tip          | 0.021" - 0.027"                         |
| Spray angle degrees | 65°- 80°                                |
| Pressure at nozzle  | 140 - 190 kg/cm <sup>2</sup> (2100 psi) |

### Conditions during application

The temperature of the substrate should be minimum 10 °C and at least 3 °C above the dew point of the air, measured in the vicinity of the substrate. Good ventilation is usually required in confined areas to ensure proper drying.

### Recommended film thickness per coat

Dry film thickness : 30 - 40 microns (µm)  
Wet film thickness : 91 - 121 microns (µm)

Film thickness will vary and is calculated as average.

### Spreading rate per coat

Theoretical Spreading rate per coat (m<sup>2</sup>/l) : 8 - 11

Spreading rate depends on film thickness applied, type of texture, surface porosity, imperfections, temperature, wastage during painting etc.

### Thinner

Water

### Dilution

The paint is ready to use after proper stirring. If thinning is required, water may be added up to a maximum of 5%.

### Drying times

Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly. The figures given in the table are typical with:

Good ventilation (Outdoor exposure or free circulation of air)

Typical film thickness

One coat on top of inert substrate

The given data must be considered as guidelines only. The actual drying time and time before recoating may be shorter or longer, depending on the ambient temperature, film thickness, ventilation, humidity, underlying paint system, requirement for early handling and mechanical strength etc. A complete system can be described on a system sheet, where all parameters and special conditions could be included.

1. Recommended data given is, for recoating with the same generic type of paint.
2. In case of multi-coat application, drying times will be influenced by the number and sequence and by the total thickness of previous coats applied.
3. The surface should be dry and free from any contamination prior to application of the subsequent coat.

#### Relative Humidity (RH) 50 %

| Substrate temperature     | 10 °C | 23 °C | 40 °C |
|---------------------------|-------|-------|-------|
| Surface (touch) dry       | 2 h   | 1 h   | 0.5 h |
| Hard dry                  | 8 h   | 6 h   | 4 h   |
| Dry to over coat, minimum | 4 h   | 2 h   | 1 h   |

## Directions for use

### Surface preparation

The substrate must be sound, clean, dry and free from dust, oil, grease, laitance etc. All traces of form release agents/curing agents must be removed. A light sanding with suitable abrasive material is recommended before application. Any resulting dust/loose particles must be removed.

### Recommended paint system

#### Primer

Gardex EcoPrimer : 1 coat

#### Topcoat

Gardex EcoGloss : 2 coats

#### Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

### Certificates

Complies to Singapore Green Label, Malaysia SIRIM Eco-Label.

### Tests

Fungus Resistance Test measured according to SS 150 :1998 (Annex C: Mildew Resistance Test).

Volume Solids % measured according to ISO 3233:1998 (E).

### Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health- and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

### Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.



## Gardex EcoPrimer

---

### Product description

#### Type

A premium and environmentally friendly water-based acrylic primer that promotes better paint adhesion to wood and metal surfaces, and provides optimum protection in combination with Gardex EcoGloss.

#### Features and benefits

Ultra Low VOC - Surpasses international and local green buildings certification to provide better air quality indoors and outdoors.

Low Odour - Paint odour is low during and after application making the property ready for occupancy in shorter period.

Fast Drying - Convenient and quick drying solution that saves time, energy and manpower.

Anti Rust - Extends the beauty and durability of metal by protecting it from corrosion.

Tanning Blocking - Blocks wood tanning from penetrating to the topcoat so as to maintain the beautiful appearance.

Formulated without Harmful Chemicals - Free from harmful chemicals such as APEO, formaldehyde, heavy metals and has low volatile organic compound (VOC).

#### Recommended use

Ideally for interior ambiances, suitable for both new and painted substrate (even on existing alkyd paints which is in good condition).

#### Substrate

On wood and metal surfaces.

### Product data

|                       |                |
|-----------------------|----------------|
| <b>Packaging size</b> | 5L.            |
| <b>Colours</b>        | White.         |
| <b>Solids</b>         | 36 ± 2 volume% |

### Application data

#### Remarks

Handle with care. Stir well before use.

#### Application methods

By brush, roller, airless spray or conventional spray.

#### Guiding data for airless spray

|                            |                 |
|----------------------------|-----------------|
| <b>Nozzle tip</b>          | 0.021" - 0.027" |
| <b>Spray angle degrees</b> | 65°- 80°        |

# Technical Data Sheet

## Gardex EcoPrimer



**Pressure at nozzle** 140 - 190 kg/cm<sup>2</sup> (2100 psi)

### Conditions during application

The temperature of the substrate should be minimum 10 °C and at least 3 °C above the dew point of the air, measured in the vicinity of the substrate. Good ventilation is usually required in confined areas to ensure proper drying.

### Recommended film thickness per coat

Dry film thickness : 30 - 50 microns (µm)  
Wet film thickness : 83 - 139 microns (µm)

Film thickness will vary and are calculated as an average.

### Spreading rate per coat

Theoretical Spreading rate per coat (m<sup>2</sup>/l) : 7.2 - 12

Spreading rate depends on film thickness applied, type of texture, surface porosity, imperfections, temperature, wastage during painting etc.

### Thinner

Water

### Dilution

The paint is ready to use after proper stirring. If thinning is required, water may be added up to a maximum of 5%.

### Drying times

Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly.

Good ventilation (Outdoor exposure or free circulation of air)

Typical film thickness

One coat on top of inert substrate

The given data must be considered as guidelines only. The actual drying time and time before recoating may be shorter or longer, depending on the ambient temperature, film thickness, ventilation, humidity, underlying paint system, requirement for early handling and mechanical strength etc.

1. Recommended data given is, for recoating with the same generic type of paint.
2. In case of multi-coat application, drying times will be influenced by the number and sequence and by the total thickness of previous coats applied.
- 3 . The surface should be dry and free from any contamination prior to application of the subsequent coat.

### Relative Humidity (RH) 50 %

| Substrate temperature     | 10 °C | 23 °C | 40 °C |
|---------------------------|-------|-------|-------|
| Surface (touch) dry       | 2 h   | 1 h   | 0.5 h |
| Hard dry                  | 8 h   | 6 h   | 4 h   |
| Dry to over coat, minimum | 4 h   | 2 h   | 1 h   |

## Directions for use

### Surface preparation

The substrate must be sound, clean, dry and free from dust, oil, grease, laitance etc. All traces of form release agents/curing agents must be removed. A light sanding with suitable abrasive material is recommended before application. Any resulting dust/loose particles must be removed.

### Recommended paint system

#### Primer



# Technical Data Sheet

## Gardex EcoPrimer



Gardex EcoPrimer : 1 coat

Remark: For dark wood, it is recommended to use 2 coats of primer to achieve good tannin blocking property.

### Topcoat

Gardex EcoGloss : 2 coats

### Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

## Certificates

Complies to Singapore Green Label, Malaysia SIRIM Eco-Label.

## Tests

Volume Solids % measured according to ISO 3233:1998 (E).

## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health- and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

## Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.



Our reference: QAPD/MM/271115-1  
Date: 27 Nov. 2015

**TO WHOM IT MAY CONCERN**

Dear Sir/Mdm,

**RE: Reinforcement Steel Bars - Recycled Content and GBI Data**

We are pleased to confirm that our reinforcement steel bars are manufactured from scrap iron and steel via Electric Arc Furnace process route currently with recycled content listed below:

Recycled Content

| No. | Description | Post-consumer | Pre-consumer |
|-----|-------------|---------------|--------------|
| 1   | Steel rebar | 95%           | 3~5%         |

GBI Data

| No. | Description                  | Harvest Distance | Manufacture Distance |
|-----|------------------------------|------------------|----------------------|
| 1   | Local steel scrap / iron ore | <500KM           | N/A                  |
| 2   | Steel rebar                  | N/A              | <300KM               |

The products are manufactured at our plants (Prai and Shah Alam) in Penang and Selangor respectively.

We trust the above is in order.

Please do not hesitate to contact us should you have further enquiry.

Thank you.

Yours faithfully,

Ng Beng Fooi  
Senior Manager  
Quality Assurance and Product Development

# Masteel

MALAYSIA STEEL WORKS (KL) BHD (7878-V)

Our ref : MSW/NL/040117/006

Date : 04 JAN 2017

SUNWAY MARKETING SDN, BHD,  
LEVEL 11, MENARA SUNWAY, JALAN LAGOON TIMUR,  
BANDAR SUNWAY, 47500 SELANGOR, D.E.

TO WHOM IT MAY CONCERN

Dear Sir/Madam,

Reference made to the above mentioned

We hereby confirm that the raw materials/s for reinforcement steel bars are tabulated as follow :

Name of Company : Masteel  
Tel : 03-77811611  
Fax : 03-77813679

| Item | Composition Of Raw Material |    | Recycled Content |              |
|------|-----------------------------|----|------------------|--------------|
|      |                             |    | Post-Consumer    | Pre-Consumer |
|      | Description                 | %  | %                | %            |
|      | High Tensile Deformed Bars  |    |                  |              |
| 1    | Scrap                       | 94 | 95-97%           | 3-5%         |
| 2    | Lime                        | 2  | 0%               | 0%           |
| 3    | Others                      | 4  | 0%               | 0%           |

The product has been manufactured at our mill/factory at Petaling Jaya Selangor.

We trust the above is in order and please do not hesitate to contact us should you require further clarification on the above matter.

Thank you.

Your faithfully,

MALAYSIA STEEL WORKS (KL) BERHAD

.....  
WONG CHOON FATT  
QA MANAGER

WISMA MASTEEL

29C, Off Jalan Tandang, Section 51, 46050 Petaling Jaya, Selangor Darul Ehsan, Malaysia



Brand Finance®

44 yrs  
For Excellence



TOTAL P.01



## RECYCLED CONTENT &amp; REGIONAL MATERIAL (SUPPLIER)

**Southern Steel Bldg.**

0759066-70

043852874

Confirmed By:

Signature and Stamp of Supplier  
Name: Chan Weng Weng  
Designation: Manager  
Date: 5/10/2015

Page 1 of 1





Date : 27 October 2016

To Whom It May Concern,

**Ref : STEEL WIRE RODS**

We wish to confirm that our Steel Wire Rods are manufactured from scrap iron and steel using Electric Arc Furnace with recycle content as follows :

| No | Descriptions    | Recycle Content |              |
|----|-----------------|-----------------|--------------|
|    |                 | Post-Consumer   | Pre-Consumer |
| 1  | Steel Wire Rods | 94%             | 4.3%         |

We trust the above is in order and we shall be happy to answer any queries if any on the subject matter.

Thank you.

Yours truly,

( Ooi Sau Ping )  
QA Manager

Southern Steel Rod Sdn Bhd (160697-A)



The Singapore Green Labelling Scheme Secretariat hereby grant

## **White Horse Ceramic Industries Sdn Bhd**

PLO 464, Jalan Gangsa Pasir Gudang Industrial Estate, 81700 Pasir Gudang Johor Malaysia

the right to use the Singapore Green Label for

**WHITE HORSE - MATERIE SERIES - H63043, H63044,  
H63045, H63046, H63047, H63048**

024-003-0290

**"ECO-FRIENDLY BUILDING MATERIAL"**

Validity: 1 June 2016 to 31 May 2017

EDWIN SEAH  
Executive Director  
Singapore Environment Council



Singapore  
Environment  
Council



No Lesen : EL000013

Licence No :

## LESEN PENSIJILAN EKO-LABEL

*Eco-Label Licence*



SIRIM QAS International Sdn. Bhd. dengan ini menganugerahkan kepada  
*SIRIM QAS International Sdn. Bhd. hereby grants to*

WHITE HORSE CERAMIC INDUSTRIES SDN.BHD  
PLO 464 , JALAN GANGSA , ZONE 11  
PASIR GUDANG IND ESTATE  
81700, PASIR GUDANG  
JOHOR, MALAYSIA

Lesen untuk menggunakan Tanda Eco-Label di atas barangan  
*a licence to use the Eco-Label Mark on*

CERAMIC TILES


Please refer to detail in the SCHEDULE

sebagai mematuhi keperluan  
*as complying with*

SIRIM CRITERIA 022 : 2010



Khalidah Mustafa  
Pengarah Urusan  
*Managing Director*  
SIRIM QAS International Sdn. Bhd.



SIRIM QAS International Sdn. Bhd.  
(No. Syankat 410334-X)  
1, Persiaran Dato' Menteri  
Seksyen 2, Petai Surat 7035  
40700 Shah Alam  
Selangor Darul Ehsan  
MALAYSIA.

Tel : 60-3-55446400  
Faks : 60-3-55446466

<http://www.sirim.my>  
<http://www.malaysian-certified.my>

Tarikh Mula Pensijilan : 04 May 2012

*Certified Since*

Sah Sehingga : 04 May 2018

*Valid Until*

Tarikh Dikeluarkan : 22 April 2016

*Issue Date*

No Siri : 023459

*Serial No*

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM QAS International Sdn. Bhd.  
*This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM QAS International Sdn. Bhd.*



## SCHEDULE

### WHITE HORSE CERAMIC INDUSTRIES SDN.BHD



|       |                                                                                               |
|-------|-----------------------------------------------------------------------------------------------|
| Brand | : WHITE HORSE                                                                                 |
| Model | : GROUP BIA - GLAZED<br>(THICKNESS $\geq$ 7.5MM)<br>INDICATION OF FIRST QUALITY: FIRST GRADE  |
| Size  | : NON-MODULAR: 20CM X 20CM, 30CM X 30CM                                                       |
| Brand | : WHITE HORSE                                                                                 |
| Model | : GROUP BIIA - GLAZED<br>(THICKNESS $\geq$ 7.5MM)<br>INDICATION OF FIRST QUALITY: FIRST GRADE |
| Size  | : NON-MODULAR: 20CM X 20CM, 25CM X 25CM, 40CM X 40CM                                          |
| Brand | : WHITE HORSE                                                                                 |
| Model | : GROUP BIIB - GLAZED<br>(THICKNESS $\geq$ 7.5MM)<br>INDICATION OF FIRST QUALITY: FIRST GRADE |
| Size  | : NON-MODULAR: 20CM X 20CM                                                                    |
| Brand | : WHITE HORSE                                                                                 |
| Model | : GROUP BIII - GLAZED<br>(THICKNESS $\geq$ 7.5MM)<br>INDICATION OF FIRST QUALITY: FIRST GRADE |
| Size  | : NON-MODULAR: 25CM X 33CM, 25CM X 40CM, 30CM X 30CM, 30CM X 40CM, 45CM X 45CM                |
| Brand | : WHITE HORSE                                                                                 |
| Model | : GROUP BIII - GLAZED<br>(THICKNESS $\leq$ 7.5MM) INDICATION OF FIRST QUALITY: FIRST GRADE    |
| Size  | : NON-MODULAR: 20CM X 20CM, 20CM X 25CM                                                       |

Eco-Labeling Claim : ECO-FRIENDLY CERAMIC TILES

End of page

SIRIM QAS International Sdn. Bhd.  
(No. Syarikat 410334-X)  
1, Persiaran Dato' Menteri  
Seksyen 2, Peti Surat 7035  
40700 Shah Alam  
Selangor Darul Ehsan  
MALAYSIA.

Tel : 60-3-55446400  
Faks : 60-3-55446466

<http://www.sirim.my>  
<http://www.malaysian-certified.my>

Tarikh Mula Pensijilan : 04 May 2012

Certified Since

Sah Sehingga : 04 May 2018

Valid Until

Tarikh Dikeluarkan : 22 April 2016

Issue Date

No Siri : 023459

Serial No

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM QAS International Sdn. Bhd.  
This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM QAS International Sdn. Bhd.



No Lesen : PC002649  
Licence No :

## LESEN PENSIJILAN BARANGAN

*Product Certification Licence*



SIRIM QAS International Sdn. Bhd. dengan ini menganugerahkan kepada  
*SIRIM QAS International Sdn. Bhd. hereby grants to*

**WHITE HORSE MARKETING SDN. BHD.**  
PLO 464, JALAN GANGSA  
81700, PASIR GUDANG  
JOHOR, MALAYSIA




Lesen untuk menggunakan Tanda Pensijilan di atas barangan  
*a licence to use the Certification Mark on*  
**CERAMIC TILES**

Please refer to detail in the SCHEDULE

sebagai mematuhi keperluan  
*as complying with*  
**MS ISO 13006 : 2003**

**Mohd Azanuddin bin Salleh**  
Pengarah Urusan  
Managing Director  
SIRIM QAS International Sdn. Bhd.



SIRIM QAS International Sdn. Bhd.  
(No. Syarikat 410334-X)  
1, Persiaran Dato' Menteri  
Seksyen 2, Petai Surat 7035  
40700 Shah Alam  
Selangor Darul Ehsan  
MALAYSIA.

Tel : 60-3-55446400  
Faks : 60-3-55446466

<http://www.sirim.my>  
<http://www.malaysian-certified.my>

Tarikh Mula Pensijilan : 25 November 2016  
Certified Since  
Sah Sehingga : 25 November 2017  
Valid Until

Tarikh Dikeluarkan : 07 December 2016  
Issue Date  
No Siri : 027739  
Serial No

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM QAS International Sdn. Bhd.  
*This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM QAS International Sdn. Bhd.*

## SCHEDULE

WHITE HORSE MARKETING SDN. BHD.



Brand : CAVALLO  
Model : GROUP Bla - GLAZED (THICKNESS IS MORE THAN OR EQUAL TO 7.5mm)  
INDICATION OF FIRST QUALITY: 1ST GRADE  
Rating : NON - MODULAR  
60cm X 60cm, 80cm X 80cm, 60cm X 120cm



Brand : CAVALLO  
Model : GROUP Bla - UNGLAZED POLISHED (THICKNESS IS MORE THAN OR EQUAL TO 7.5mm) INDICATION OF FIRST QUALITY: 1ST GRADE  
Rating : NON - MODULAR 60cm X 60cm, 80cm X 80cm, 60cm X 120cm  
Brand : CAVALLO  
Model : GROUP Bla - UNGLAZED NON-POLISHED (THICKNESS IS MORE THAN OR EQUAL TO 7.5mm) INDICATION OF FIRST QUALITY: 1ST GRADE  
Rating : NON - MODULAR 60cm X 60cm, 80cm X 80cm, 60cm X 120cm

Factory Name and Location :  
GUANGDONG GRIFINE CERAMICS CO. LTD  
HEFENG INDUSTRIAL ZONE, NANZHUANG TOWN  
CHANCHENG DISTRICT  
FOSHAN  
GUANGDONG, CHINA

End of page

SIRIM QAS International Sdn. Bhd.  
(No. Syarikat 410334-X)  
1, Persiaran Dato' Menteri  
Seksyen 2, Peti Surat 7035  
40700 Shah Alam  
Selangor Darul Ehsan  
MALAYSIA.

Tel : 60-3-55446400  
Faks : 60-3-55446466

<http://www.sirim.my>  
<http://www.malaysian-certified.my>

Tarikh Mula Pensijilan : 25 November 2016  
Certified Since  
Sah Sehingga : 25 November 2017  
Valid Until

Tarikh Dikeluarkan : 07 December 2016  
Issue Date  
No Siri : 027739  
Serial No

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM QAS International Sdn. Bhd.  
This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM QAS International Sdn. Bhd.





No Lesen : PW002701

Licence No :

## LESEN PENSIJILAN BARANGAN

*Product Certification Licence*



SIRIM QAS International Sdn. Bhd. dengan ini menganugerahkan kepada  
*SIRIM QAS International Sdn. Bhd. hereby grants to*

WHITE HORSE CERAMIC INDUSTRIES SDN.BHD  
PLO 29  
TANJUNG LANGSAT INDUSTRIAL ESTATE  
81700, PASIR GUDANG  
JOHOR, MALAYSIA




Lesen untuk menggunakan Tanda Pensijilan di atas barangan  
*a licence to use the Certification Mark on*  
**CERAMIC TILES**

Please refer to detail in the SCHEDULE

sebagai mematuhi keperluan  
*as complying with*  
MS ISO 13006 : 2003

*Khalidah Mustafa*

Khalidah Mustafa  
Pengarah Urusan  
Managing Director  
SIRIM QAS International Sdn. Bhd.



SIRIM QAS International Sdn. Bhd.  
(No. Syarikat 410334-X)  
1, Persiaran Dato' Menteri  
Seksyen 2, Peti Surat 7035  
40700 Shah Alam  
Selangor Darul Ehsan  
MALAYSIA.

Tel : 60-3-55446400  
Faks : 60-3-55446466

<http://www.sirim.my>  
<http://www.malaysian-certified.my>

Tarikh Mula Pensijilan : 14 March 2003  
Certified Since  
Sah Sehingga : 14 March 2017  
Valid Until

Tarikh Dikeluarkan : 13 April 2016  
Issue Date  
No Siri : 023228  
Serial No

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM QAS International Sdn. Bhd.  
*This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM QAS International Sdn. Bhd.*



## SCHEDULE

### WHITE HORSE CERAMIC INDUSTRIES SDN.BHD



Brand : WHITE HORSE  
Model : GROUP BIA - GLAZED (THICKNESS MORE THAN OR EQUAL TO 7.5MM)  
INDICATION OF FIRST QUALITY : FIRST GRADE  
Rating : NON-MODULAR 20CM X 20CM, 30CM X 30CM

Brand : WHITE HORSE  
Model : GROUP BIIA - GLAZED (THICKNESS MORE THAN OR EQUAL TO 7.5MM)  
INDICATION OF FIRST QUALITY : FIRST GRADE  
Rating : NON-MODULAR 20CM X 20CM, 25CM X 25CM, 30CM X 30 CM, 40CM X 40CM, 50CM X 50CM



Brand : WHITE HORSE  
Model : GROUP BIIB - GLAZED (THICKNESS MORE THAN OR EQUAL TO 7.5MM)  
INDICATION OF FIRST QUALITY : FIRST GRADE  
Rating : NON-MODULAR 20CM X 20CM

Brand : WHITE HORSE  
Model : GROUP BIIC - GLAZED (THICKNESS MORE THAN OR EQUAL TO 7.5MM)  
INDICATION OF FIRST QUALITY : FIRST GRADE  
Rating : NON-MODULAR 25CM X 33CM, 25CM X 40CM, 30CM X 30CM, 30CM X 40CM, 30CM X 45CM, 45CM X 45CM

Brand : WHITE HORSE  
Model : GROUP BIID - GLAZED (THICKNESS LESS THAN 7.5MM) INDICATION OF FIRST QUALITY : FIRST GRADE  
Rating : NON-MODULAR 20CM X 20CM, 20CM X 25CM

#### Factory Name and Location :

**WHITE HORSE CERAMIC INDUSTRIES SDN.BHD**

**PLO 464, JALAN GANGSA  
ZONE 11, PASIR GUDANG INDUSTRIAL ESTATE  
81700, PASIR GUDANG  
JOHOR, MALAYSIA**

End of page

SIRIM QAS International Sdn. Bhd.  
(No. Syarikat 410334-X)  
1, Persiaran Dato' Menteri  
Seksyen 2, Peli Surat 7035  
40700 Shah Alam  
Selangor Darul Ehsan  
MALAYSIA.

Tel : 60-3-55446400  
Faks : 60-3-55446466

<http://www.sirim.my>  
<http://www.malaysian-certified.my>

Tarikh Mula Pensijilan : 14 March 2003  
Certified Since  
Sah Sehingga : 14 March 2017  
Valid Until

Tarikh Dikeluarkan : 13 April 2016  
Issue Date  
No Siri : 023228  
Serial No

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM QAS International Sdn. Bhd.  
This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM QAS International Sdn. Bhd.



No Lesen : PW016601

Licence No :

## LESEN PENSIJILAN BARANGAN

*Product Certification Licence*



SIRIM QAS International Sdn. Bhd. dengan ini menganugerahkan kepada  
*SIRIM QAS International Sdn. Bhd. hereby grants to*

WHITE HORSE CERAMIC INDUSTRIES (VN) CO.LTD  
STREET 2A, MY XUAN A INDUSTRIAL PARK  
MY XUAN WARD  
TAN THANH DISTRICT  
BA RIA VUNG TAU PROVINCE, VIETNAM




Lesen untuk menggunakan Tanda Pensijilan di atas barangan  
*a licence to use the Certification Mark on*  
**CERAMIC TILES**

Please refer to detail in the SCHEDULE

sebagai mematuhi keperluan  
*as complying with*  
MS ISO 13006 : 2003

Mohd Azanuddin bin Salleh  
Pengarah Urusan  
*Managing Director*  
SIRIM QAS International Sdn. Bhd.



SIRIM QAS International Sdn. Bhd.  
(No. Syankat 410334-X)  
1, Persiaran Dato' Menteri  
Seksyen 2, Peti Surat 7035  
40700 Shah Alam  
Selangor Darul Ehsan  
MALAYSIA.

Tel : 60-3-55446400  
Faks : 60-3-55446466

<http://www.sirim.my>  
<http://www.malaysian-certified.my>

Tarikh Mula Pensijilan : 08 October 2010  
*Certified Since*  
Sah Sehingga : 08 October 2017  
*Valid Until*

Tarikh Dikeluarkan : 07 September 2016  
*Issue Date*  
No Siri : 026042  
*Serial No*

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM QAS International Sdn. Bhd.  
*This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM QAS International Sdn. Bhd.*

## SCHEDULE

### WHITE HORSE CERAMIC INDUSTRIES (VN) CO.LTD



Brand : WHITE HORSE, FREYA, CAVALLO  
Model : GROUP BIa - GLAZED (THICKNESS IS MORE THAN OR EQUAL TO 7.5mm)  
INDICATION OF FIRST QUALITY : 1ST GRADE, GRADE 1  
Rating : NON - MODULAR  
15cm X 60cm, 40cm X 40cm, 45cm X 45cm, 30cm X 60cm, 60cm X 60cm



Brand : WHITE HORSE, FREYA, CAVALLO  
Model : GROUP BIib - GLAZED (THICKNESS IS MORE THAN OR EQUAL TO 7.5mm)  
INDICATION OF FIRST QUALITY : 1ST GRADE, GRADE 1  
Rating : NON - MODULAR  
40cm X 40cm, 50cm X 50cm

Brand : WHITE HORSE, FREYA, CAVALLO  
Model : GROUP BIii - GLAZED (THICKNESS IS MORE THAN OR EQUAL TO 7.5mm)  
INDICATION OF FIRST QUALITY: 1ST GRADE, GRADE 1  
Rating : NON - MODULAR  
20cm X 40cm, 25cm X 40cm, 30cm X 30cm, 30cm X 45cm, 30cm X 60cm, 30cm X 90cm, 40cm X 40cm, 50cm X 50cm

Brand : WHITE HORSE, FREYA, CAVALLO  
Model : GROUP BIa - UNGLAZED POLISHED (THICKNESS IS MORE THAN OR EQUAL TO 7.5mm) INDICATION OF FIRST QUALITY : 1ST GRADE, GRADE 1  
Rating : NON - MODULAR  
60cm X 60cm

End of page

SIRIM QAS International Sdn. Bhd.  
(No. Syarikat 410334-X)  
1, Persiaran Dato' Menteri  
Seksyen 2, Peli Surat 7035  
40700 Shah Alam  
Selangor Darul Ehsan  
MALAYSIA.

Tel : 60-3-55446400  
Faks : 60-3-55446466

<http://www.sirim.my>  
<http://www.malaysian-certified.my>

Tarikh Mula Pensijilan : 08 October 2010

Certified Since

Sah Sehingga : 08 October 2017

Valid Until

Tarikh Dikeluarkan : 07 September 2016

Issue Date

No Siri : 026042

Serial No

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM QAS International Sdn. Bhd.  
This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM QAS International Sdn. Bhd.



No Lesen : PW002703

Licence No :

## LESEN PENSIJILAN BARANGAN

*Product Certification Licence*



SIRIM QAS International Sdn. Bhd. dengan ini menganugerahkan kepada  
*SIRIM QAS International Sdn. Bhd. hereby grants to*

WHITE HORSE CERAMIC INDUSTRIES SDN.BHD  
PLO 29, TANJUNG LANGSAT INDUSTRIAL ESTATE  
81700, PASIR GUDANG  
JOHOR, MALAYSIA



Lesen untuk menggunakan Tanda Pensijilan di atas barangan  
*a licence to use the Certification Mark on*  
CERAMIC TILES

Please refer to detail in the SCHEDULE

sebagai mematuhi keperluan  
*as complying with*  
MS ISO 13006 : 2003

*Khalidah Mustafa*

Khalidah Mustafa  
Pengarah Urusan  
Managing Director  
SIRIM QAS International Sdn. Bhd.

SIRIM QAS International Sdn. Bhd.  
(No. Syarikat 410334-X)  
1, Persiaran Dato' Menteri  
Seksyen 2, Peli Surat 7035  
40700 Shah Alam  
Selangor Darul Ehsan  
MALAYSIA

Tel : 60-3-55446400  
Faks : 60-3-55446466

<http://www.sirim.my>  
<http://www.malaysian-certified.my>

Tarikh Mula Pensijilan : 29 April 2005

*Certified Since*

Sah Sehingga : 29 April 2017

*Valid Until*

Tarikh Dikeluarkan : 13 April 2016

*Issue Date*

No Siri : 023220

*Serial No*

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM QAS International Sdn. Bhd.  
*This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM QAS International Sdn. Bhd.*





No Lesen : PW002703  
Licence No :

# SCHEDULE

## WHITE HORSE CERAMIC INDUSTRIES SDN.BHD



Brand : WHITE HORSE  
Model : GROUP BIA - GLAZED (THICKNESS MORE THAN OR EQUAL TO 7.5MM)  
INDICATION OF FIRST QUALITY : FIRST GRADE  
Rating : NON-MODULAR 30CM X 30CM, 30CM X 60CM, 60CM X 60CM, 80CM X 80CM, 30CM X 90CM, 60CM X 90CM, 60CM X 120CM



Brand : WHITE HORSE  
Model : GROUP BIA - UNGLAZED POLISHED (THICKNESS MORE THAN OR EQUAL TO 7.5MM) INDICATION OF FIRST QUALITY : FIRST GRADE  
Rating : NON-MODULAR 30CM X 60CM, 60CM X 60CM, 80CM X 80CM, 60CM X 120CM  
Brand : WHITE HORSE  
Model : GROUP BIIA - GLAZED (THICKNESS MORE THAN OR EQUAL TO 7.5MM) INDICATION OF FIRST QUALITY : FIRST GRADE  
Rating : NON-MODULAR 50CM X 50CM, 30CM X 60CM

End of page

SIRIM QAS International Sdn. Bhd.  
(No. Syarikat 410334-X)  
1, Persiaran Dato' Menteri  
Seksyen 2, Petai Surut 7035  
40700 Shah Alam  
Selangor Darul Ehsan  
MALAYSIA.

Tel : 60-3-55446400  
Faks : 60-3-55446466

<http://www.sirim.my>  
<http://www.malaysian-certified.my>

Tarikh Mula Pensijilan : 29 April 2005  
Certified Since  
Sah Sehingga : 29 April 2017  
Valid Until

Tarikh Dikeluarkan : 13 April 2016  
Issue Date  
No Siri : 023220  
Serial No

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM QAS International Sdn. Bhd.  
This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM QAS International Sdn. Bhd.